

511 "L" Block Table Top Shield

Provides maximum protection for safe handling of 511 KeV nuclides.

The newly designed 511 "L" Block Shield is placed in front of the Drawing Station and used to provide a protected work area for safe handling of 511 keV nuclides. The front wall and the base of the unit are constructed of steel with built-in lead shielding. A 4" thick lead glass window offers maximum protection and an unrestricted viewing area. In addition, the lead glass is protected from scratches and chips by a sheet of window glass.



FEATURES

- The fixed angle design of the lead glass allows easier viewing.
- Contains two sheets of 1/4" window glass to protect lead glass from scratching and chips (Industry exclusive).

SPECIFICATIONS

- 14" w x 14" d x 20 1/4" h.
- 8" w x 8" h x 4" thick 5.2 g/cc density lead glass.
- Weight: 195 lbs.

Optional Brick Kits for 511 "L" Block.

1. 28" w x 16" d x 12" h x 2" thick Unpainted Chevron Brick Kit (5530-1029).
2. 28" w x 16" d x 12" h x 2" thick Painted Chevron Brick Kit (5530-1030).
3. 28" w x 16" d x 12" h x 2 3/8" thick Unpainted Chevron Brick Kit (5530-1035).
4. 28" w x 16" d x 12" h x 2 3/8" thick Painted Chevron Brick Kit (5530-1036).

511 Adjustable "L" Block Table Top Shield

Excellent radiation protection with exceptional flexibility

Capintec is very pleased to introduce our first Adjustable 511 L Block Table Top Shield. Designed to exceed the basic requirement of outstanding radiation protection it now also boasts the luxury of an adjustable lead glass window for greater work area flexibility. The front wall shields with 2 3/8" thick lead and the window is 4" thick lead glass, with a clear glass cover to protect it from scratching. The front, base and glass frame are each constructed of high gauge steel for superior strength and stability.

Use the Adjustable L Block in conjunction with the Capintec Dose Drawing Station or as a stand-alone unit. Either way, the optional Brick Kits (for side and back wall protection) will provide the perfect finishing touch for your 511 Adjustable L Block.

The 511 "L" Block Shield is shipped in three pieces and easily assembled on site. Side walls are available as an option.



FEATURES

- Adjustable lead glass window from 30-55 degrees.
- Clear glass covering to protect lead glass from chipping and scratching.
- Steel construction for strength and stability.

SPECIFICATIONS

- 2-3/8" Lead Shielding
- 8" x 8" x 4" lead glass (5.2 density, 1.6" lead equivalence)
- Adjustable window angle of 30-55 degrees with respect to vertical
- 15-3/4" W x 15-1/2" D x 21" H
- Weight - 500lbs.

ITEM #	DESCRIPTION
0665-2014	PET L-Block Shield w/4" glass
5530-2077	511 Adjustable "L" Block Shield